

Domain Renew

Table of contents

- 1 [Description](#)
- 2 [Additional Information](#)
- 3 [XML Example](#)

Description

The domain renew command extends the current registration period. The registration period value is always a time unit of one or more years

Additional Information

- The possible registration period values depend on the respective TLD.



Note

If a domain has the status pendingDelete and you send a domain renew command with a domain registration period value of 0, the cancelation is removed and the domain continues to exist normally. In this case the response is asynchronous.

XML Example

Domain Renew Request

```
<epp xmlns="urn:ietf:params:xml:ns:epp-1.0">
  <command>
    <renew>
      <domain:renew xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
        <domain:name>example.com</domain:name>
        <domain:curExpDate>2020-05-22</domain:curExpDate>
        <domain:period unit="y">1</domain:period>
      </domain:renew>
    </renew>
    <clTRID>ABC-12345</clTRID>
  </command>
</epp>
```

Domain Renew Response

```
<epp xmlns="urn:ietf:params:xml:ns:epp-1.0" xmlns:domain="urn:ietf:params:xml:ns:domain-1.0">
  <response>
    <result code="1001">
      <msg lang="en">Command completed successfully; action pending</msg>
    </result>
    <resData>
      <domain:renData>
        <domain:name>example.com</domain:name>
        </domain:renData>
      </resData>
      <extension />
      <trID>
        <clTRID>ABC-12345</clTRID>
      </trID>
    </response>
  </epp>
```